

UT125C is a pocket size, ergonomic and reliable multimeter with 4000 display counts. It is a useful tool for electronics DIYers working with low currents (<0.4A).

This product is CE/cETLus certified and complies with CAT III 600V.



UT125C

Specifications	Range	Accuracy
<b>Certificates</b>	CE, UKCA, cETLus	
DC voltage (V)	600V	±(0.5%+5)
AC voltage (V)	600V	±(1.2%+5)
DC current (A)	400mA	±(1.8%+5)
AC current (A)	400mA	±(2%+8)
Resistance (Ω)	40MΩ	±(1%+5)
Capacitance (F)	100μF	±(4%+10)
Frequency (Hz)	10Hz~60kHz	±(0.1%+5)
Duty cycle	20%~80%	Reference
Operating temperature	0°C~50°C	
Category ratings	CAT III 600V	



Features	
NCV	Diode test/Continuity test
Low battery indication	Data hold/backlight

Characteristics	
Standard accessories	Batteries, English manual
Power	1.5V battery (R03) x 2
Display	38 x 23mm
Product size	112 x 58 x 35mm
Product net weight	180g
Standard individual packing	Gift box
Standard quantity per carton	60pcs
Standard carton measurement	500 x 290 x 280mm
Standard carton gross weight	13.5kg

